
23*22ft Double Garage Metal Shed Installation Instructions



Thank you for choosing us! It will take 8-12 hours for 4-5 people to install.

The product comes in one box. Please install on a leveled place.

Make sure bolt the expansion screws into the ground to prevent the wind from collapsing.

Before Assembly

Building codes: Before construction, please check the local building codes regardingfootings, location and other requirements.

Weather: Do not install on any windy or rainy day which may cause damages on thewalls and even serious danger to the builders.

Teamwork: You need two or more people to work together to assemble and finish your building.

Parts and Parts List: Check all parts one by one according to the Parts List and make sure no parts are missing.

Note: Extra fasteners are included.

Tips: Distinguish components and accessories by the part numbers while reviewing Parts List. Familiarize yourself with all parts for easier use during construction.

Assembly instructions: Instructions, tips and important information are supplied in this manual. Please read and follow the instructions carefully to finish the assembly correctly and smoothly.

Site Selection & Preparation

Avoid overhanging trees as much as possible as leaves will make regular cleaning necessary and broken branches are a potential hazard. One small trees, bushes or fences nearby can be helpful, acting as a wind break.

The site must be prepared so that the base of the shed is level all round and checking with a spirit level is required. The base can be constructed by treated timber or concrete in order to stop the moisture getting into the shed.

The shed is not designed to be built onto lawn directly. Also the ground will get muddy during rainy days. If a concrete pad is made, it is important that this slopes towards the edges to prevent water.

Time must be allowed for any concrete or cement to dry before building the shed on top.

Bases can also be constructed from bricks, blocks, or mounted on a concrete pad. The bricks or blocks should be cemented onto firm and level concrete footings.

Installation Notes

Please check the quantity of all parts before installation (refer to the Parts Lists) and the appearance of the products. Make sure the product is correct before installation.

Make sure the colored panels are facing outwards and all the holes match. The panels are textured, please install the panels in the order specified in the instructions. All lines and holes should be matched to make the storage shed more stable.

For waterproof purpose, pls make sure use waterproof gaskets for each screw. Waterproof tape must be applied when assembling the ridge.

Please ensure that all screws are tightened to prevent the product from falling apart. There is a protective film on the surface to protect the product, you can keep it to protect or tear it off after installation.



We recommend two adults to complete the installation. Two adults installed together will make the installation process easier and safer.

The gloves must be carried to prevent handcuts during installation. Take care when using power tools near water. Please use the electric driver carefully during screwing to prevent the screw from slipping and hurting your hand.

Be careful not to fall when installing the roof. Please steady the ladder and make sure the product placed on a flat ground.

Please prepare below tools before installation. (Not Included)



MAINTENANCE:

Finish: Clean and wax the exterior surface periodically for a longer usage life. Touch up any scratches on the shed following steps: a) immediately clean the area with a wirebrush; b) was hit and apply touch-up paint which is applicable.

Roof: keep roof clear of leaves or snow with long handled, soft-bristled broom. Heavy snow on roof may damage the building and make it unsafe to enter.

We recommend you purchase other strengthening kits or take other protection measures if needed to protect the shed against heavy snow accumulation

Fasteners: Use all washers supplied to protect against weather infiltration or scratches by screws.

Regularly check your building for any loose screws, bolts, nuts, etc. and re-tighten them as necessary.


Moisture: It is highly recommended that a moisture proof pad displaced above the entire floor area with good ventilation to reduce condensation.

(Note: the moisture proof pad is not included in the packaging and needs to be purchased separately).

Other tips & notes:

- ·Inked part numbers on coated panels could be washed off with soap and water.
- .Silicone caulking maybe used for watertight seals throughout the building.
- Do not store any swimming pool chemicals in your shed. Combustibles and corrosives must be stored in airtight approved containers before storing in the shed.

FRAME STRUCTURE DIAGRAM




Parts List (1)

Part	No	Qty	Part	No	Qty	Part	No	Qty
	A01	1		В07	2		B27	40
	A02	1		B08	2		B28	1
f	A03	1		B09	2		B29	8
	A04	1		B10	2		B35	20
1	A05	2		B11	1		B36	3
	A06	2	9	B12	2		B37	4
(F. 168	A07	2	000	B13	6	0 0	B40	16
	A08	2	000	B14	22		D9	1
	A09	1		B15	4		F1	26
	A10	1		B16	2		F2	16
	A11	1		B17	2		F6	22
	A12	2		B18	5		F7	1152
	A13	1	0 0 0	B19	1		F11	22
	B01	13		B20	8		F12	2
	B02	6		B21	8		F17	2
0000	В03	42		B23	8	0	F18	12
	B04	12		B24	16	0	F19	10
	B05	4		B25	8		GB	1
	B06	4		B26	48		Н	1


Parts List (2)

Part	No	Qty	Part	No	Qty	Part	No	Qty
1	J1	1172		T14	2		W05	2
E Gamanananananananananananananananananana	J2	258	0	T15	38		W06	2
	J3	258		T16	1		W07	2
	J4	258		T17	1		W08	2
	J5	19		T18	1		W09	2
	S1	3		T19	1		W10	2
	T01	4	_	T20	2		W11	2
	T02	4		T21	9		W12	2
	T03	2		T22	1		W13	2
	T05	5		T23	2		W14	24
	T06	1.0	°	T24	2		W15	4
	T07	4		T25	2		W16	2
	T08	2		T26	1	~	W17	2
	Т09	4		T27	4		W18	1
	T10	2		W01	16		W19	3
	T11	11	~	W02	16		W20	1
	T12	8	~~~~	W03	10		G1	8
	T13	8		W04	5			


STEP 1: FOOT TUBE AND BASE PLATE INSTALLATION.



Part	No	Qty	Part	No	Qty
A01		1	A07	E	2
A02		1	A08	C: ::1	2
A03		1	A10		1
A04		1	A11		1
A05	c	2			
A06		2			



Part	No	Qty
B01		9
J1		66



J3


J4


B24

48


48

16






STEP 3: Install The Front Arch Frame




Note: Inside lock with J1, outside is not locked





Part	No	Qty
J2	0	8
J3		8
J4	©	8
J1		8
A12		2
B01		2
B03		2

Insert B03 into B07 and A12 then fasten with J2,J3,J4.





Insert B01 into B06 around 3.9" deep then fasten with J1.







Part	No	Qty
J2	0	8
J3		8
J4		8
B02		1
B03		4
B04		2
B05		2









Part	No	Qty
J2	0	8
J3		8
J4		8
B11		1
B10		2
A13	R. B.	1







Part	No	Qty
J1		5
B19		1


B19 Installed inside






Part	No	Qty
J1		8
B35	Chief of the Control	2
J2	0	8
J3		8
J4		8
B03		2
A13	IB IB	1
B08		2








STEP 4: Install The Back Arch Frame




Part	No	Qty
B03		6
J2	0	16
J3		16
J4		16
B04		2
B05		2
B02		1









Part	No	Qty
J1	0	16
B13		4
B16		2
B17		3



B13 Installed inside




Part	No	Qty
J1		8
B06		2





B06


Insert B01 into B06 around 3.9" deep then fasten with J1.




Part	No	Qty
B03		4
J2	0	16
J3		16
J4		16
B15		4
B16		2
B17		2
B35		4
J1		16










Part	No	Qty
J2		12
J3		12
J4		12




STEP 5: Top And Side Cross Bar Installation.










Part	No	Qty
G1		8













Part	No	Qty
J1		10
Т03		2
Т06		1
Т08		2
T10		2




Note: T03 & T06 snap directly onto B12&A13.










STEP 6: Roof Panel Installation. **W2**


Note: Panels should be stuck in B37.




192

F7

Note: Install W02 first, then Put W01 upon W02 to prevent leaking. F7 must be used to prevent leaking too.




tape H to the gap between the two tiles, then install T11.




Part	No	Qty	
W04		5	
J1		48	
F7		48	
W05		1	
W06		1	
W07		1	W04 W04 W04 W04
W08		1	
W09		1	
W10		1	
W11		1	
W12		1	
W13		1	
C		W13 V	V12 W11 W10 W06 W07 W08 W9

STEP 8 : Side Wall Panel Installation (without door).




Part	No	Qty
W14		15
J1		72
F7		72

STEP 9: Side Wall Panel Installation (with door).




Part	No	Qty
W14		9
J1		72
F7		72
W19		3
W20		1

STEP 9: Side Wall Panel Installation (with door).




STEP 10: Front Door Panel Installation.




Part	No	Qty
J1	0	108
F7		108
W05		1
W06		1
W07		1
W08		1
W09		1
W10		1


Part	No	Qty
W11		1
W12		1
W13		1
W15	~	4
W16		2
W17		2
W18		1

STEP 11: Install The Top Wrapping Strip







Note:T15 is used to reinforce decorative strips




STEP 12: Install The Wall Wrapping Strip



Part	No	Qty
J1		81
T01		4
T02		4
Т07		4
Т09		4




STEP 13: Install SideTrim Strips





STEP 14: Door Assembly - Side Door


			T20	
Part	No	Qty		
T20		2		
T21		1	T21	
T22		1	T22	
T19	~	1		
F1		16		
F2		8	T19	
F6		8		
			T20	
•	F6 F2			




Part	No	Qty
T25		2
T26		1
F2		28
F6		28
F1		8
T23		2
T24		2










Part	No	Qty
D9		7
GB		1
F12		2
F17		2
F11		11
S1		3





Part	No	Qty
F11		9





Part	No	Qty
F11		2

